Road to Confidence in IT Systems: SAMATE's SATE and SRD projects

Paul E. Black

paul.black@nist.gov




Software Assurance Metrics And Tool Evaluation (SAMATE) project

Current Areas of Concentration


- Static source code security analyzers
- Static Analysis Tool Exposition (SATE)
- SAMATE Reference Dataset (SRD)
- Vote tools evaluation methodology
- Studies

http://samate.nist.gov/

SAMATE's Niche



What is a Static Analyzer?



- Static analyzers check programs for bugs.
- They can't catch everything
 - e.g. sending data: should it be encrypted?

How Good are Static Analyzers?

- Does this analyzer find all bugs?
 - without too many false positives ...
- Does it find all the bugs we know about?
- How well does it do for important bugs?
- How much is my confidence increased by using it?
- Is running it a good use of my time?

Static Analysis Tool Exposition SATE

Goals:

- Gather large test sets to enable empirical research
- Encourage improvement of tools
- Speed adoption of tools by objectively demonstrating their use on real software

Steps

- We choose open source programs with security implications
- Participants run tools and return reports
- We analyze reports
- Everyone shares observations at a workshop
- We release final reports and data later


http://samate.nist.gov/SATE.html

SATE Overview

- We held four SATEs since 2008.
- Test sets were in C/C++, Java, and PHP and consisted of about 26,000,000 LoC.
- 19 teams on 4 continents participated.
- We received a combined 128,043 warnings*

 We better understand subtleties of finding, designating, and counting weaknesses.

How can We Test Static Analyzers?



- Come up with a small set of test programs with known bugs.
- The result of running a tool on the set is correlated with the result on large, realworld programs.

SAMATE Reference Dataset (SRD)

SRD Home View / Download Search / Download	
Search / Download	More Downloads Submit Test Suites
Extended Search Source Code Search	
Number (Test case ID):	Weakness Code Complexity
	E-Any
Description contains :	CWE-485: Insufficient Encapsulation
Contributor/Author :	E-CWE-388: Error Handling
Continuation/Author .	±- CWE-389: Error Conditions, Return Values, Status Codes
Bad / Good : Any ▼	CWE-254: Security Features
	CWE-227: Failure to Fulfill API Contract (API Abuse)
Language: Any	■ CWE-019: Data Handling ■ CWE-361: Time and State
Type of Artifact : Any →	E- CWE-398: Indicator of Poor Code Quality
CO) (00 - 10 - 10 - 10 - 10 - 10 - 10 - 10	CWE 470: Use of Externally Controlled Input to Select Class
Status : Candidate 🗹 Approv	red +- CWE-465: Pointer Issues
Weakness: Apy	±- CWE-411: Resource Locking Problems
Any	CWE-401: Failure to Release Memory Before Removing La
Code complexity: Any	- CWE-415: Double Free
B-4-	CWE-416: Use After Free
Date: Any Before (Format: M/d/Y)	After ±-CWE-417: Channel and Path Errors
use the calendar (next icon).	
Search Test Cases	

Public repository of over 60,000 test cases in C++, C, Java, C#, PHP, etc. covering 147 classes of weaknesses.

- User can search by language, weakness, code construct, etc.
- Contributions from Fortify, Defence R&D Canada, Klocwork, MIT Lincoln Laboratory, Praxis, Secure Software, and others.

samate.nist.gov/SRD

58	2005-11-02	Java	Source Code	SecureSoftware	C	Not using a a random initialization vector with Cipher Block	
71	2005-11-07	Java	Source Code	SecureSoftware	C	Omitting a break statement so that one may fall through is often	
1552	2006-06-22	Java	Source Code	Jeff Meister	C	Tainted input allows arbitrary files to be read and written.	
1553	2006-06-22	Java	Source Code	Jeff Meister	C	Tainted input allows arbitrary files to be read and written	
1554	2006-06-22	Java	Source Code	Jeff Meister	C	Two file operations are performed on a filename, allowing a filenamer	
1567	2006-06-22	Java	Source Code	Jeff Meister	C	The credentials for connecting to the database are hard-wired	
1568	2006-06-22	Java	Source Code	Jeff Meister	C	The credentials for connecting to the database are hard-wired	
1569	2006-06-22	Java	Source Code	Jeff Meister	C	The credentials for connecting to the database are hard-wired	
1570	2006-06-22	Java	Source Code	Jeff Meister	C	An exception leaks internal path information to the user.	
1571	2006-06-22	Java	Source Code	Jeff Meister	C	An exception leaks internal path information to the user. (fixed	/
1579	2006-06-22	Java	Source Code	Jeff Meister	С	Tainted output allows log entries to be forged.	

```
public class File: bad extends httpserviet
    public void doGet(HttpServletRequest req, HttpServletResponse res)
         throws ServletException, IOException
        res.setContentType("text/html");
         ServletOutputStream out = res.getOutputStream();
         out.println("<HTML><HEAD><TITLE>Test</TITLE></HEAD><BODY><blockquote>");
                  String name = reg.getParameter("name");
                  String msg = req.getParameter("msg");
                  if(name != null) {
                           try {
                                    File f = new File("/tmp", name);
                                                                                     /* BAD */
                                    if(msg != null) {
                                                                                    /* BAD */
                                             FileWriter f_W = new FileWriter(f);
                                             fw.write(msq, 0, msq.length());
                                             fw.close();
                                             out.println("message stored");
                                    } else {
                                             String line;
                                             BufferedReader fr = new BufferedReader(new FileReader(f));
                                             while((line = fr.readLine()) != null)
                                                       out.println(line);
                             catch(Exception e) {
                                    throw new ServletException(e);
```